

## FIREVIEW INSET STOVES - SPECIFICATIONS

<u>Fireview Model</u>	<u>4.0Kw</u> Curved canopy		<u>4.0Kw</u> Flat canopy		<u>6.5Kw</u> Curved canopy		<u>6.5Kw</u> Flat canopy	
	inches	mm	inches	mm	inches	mm	inches	mm
<u>OVERALL HEIGHT</u>	32.50	825	27.50	695	32.50	825	27.50	695
<u>OVERALL WIDTH</u>	30.75	780	30.75	780	30.75	780	30.75	780
<u>OVERALL DEPTH</u>	15.50	395	15.50	395	17.75	450	17.75	450
Height - rear box	20.50	520	20.50	520	21.50	540	21.50	540
Width - rear box	14.50	365	14.50	365	15.75	400	15.75	400
Depth - rear box	10.00	255	10.00	255	12.00	305	12.00	305
Maximum log length	10.00	255	10.00	255	18.00	457	18.00	457
ROOM OUTPUT WHEN FITTED WITH 30,000BTU FULL WRAP BOILER	-		-		2.10Kw		2.10Kw	

One of the easiest stoves to fit, the 4.0Kw low profile 'Easy' Inset stove fits straight into any standard fireplace and chimney with only a 4.5" (114.3mm) body projection onto the hearth. For real fire heating in your living room, or to top up the central heating, there could be nothing easier.

The 6.5Kw Inset stove relies on a full builder's opening and does not need the firebrick in place. There is also the option of fitting a 30,000Btu boiler to allow that extra piping hot water warmth to be transmitted to other parts of the home and to the hot water cylinder.

Inset stoves are vermiculite lined for increased heat efficiency and, to ensure airtight construction, incorporate fully welded seams. For stress free operation and maintenance, they feature the Woodwarm multifuel grate system and clean burn airwash.

A wide range of Stovebright colours from Mojave Red through to Forest Green is available to order.