

FIREVIEW FREESTANDING STOVES - SPECIFICATIONS

Fireview Model	<u>4.5Kw</u>		<u>6.0Kw</u>		<u>9.0Kw</u>		<u>12.0Kw</u>		<u>16.0Kw</u>		<u>20.0Kw</u>	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
Maximum log length	10.24	260	14.49	368	16.93	430	19.00	483	23.15	558	25.00	635
<u>OVERALL HEIGHT</u>												
Flat top	20.59	523	22.99	584	26.37	670	26.38	670	29.76	756	29.76	756
Low curved canopy	27.16	690	32.68	830	37.00	940	37.00	940	42.00	1067	42.00	1067
High curved canopy	n/a	n/a	37.00	940	41.14	1045	41.93	1065	n/a	n/a	n/a	n/a
<u>OVERALL WIDTH</u>												
Flat top	16.65	423	21.57	548	25.00	635	26.50	673	29.00	737	31.26	794
Low curved canopy	19.06	484	23.50	597	27.75	705	29.45	748	32.00	813	34.06	865
High curved canopy	n/a	n/a	23.35	593	27.95	710	29.45	748	n/a	n/a	n/a	n/a
<u>OVERALL DEPTH</u>												
Flat top	14.37	365	15.08	383	15.20	383	18.00	457	18.00	457	19.76	502
Low curved canopy	14.76	375	15.39	391	16.00	406	19.52	496	19.53	496	21.26	540
High curved canopy	n/a	n/a	15.94	405	16.14	410	19.13	486	n/a	n/a	n/a	n/a
Flue outlet size	5.00	127	6.00	152	6.00	152	6.00	152	7.00	177	7.00	177
Rear flue height centre	13.26	337	18.11	460	18.63	473	18.63	473	20.27	515	20.28	515
<u>TOP FLUE CENTRE LINE TO REAR</u>												
Flat top	5.00	127	6.14	156	6.14	156	6.14	156	6.73	171	6.73	171
Low curved canopy	4.13	105	4.63	117.5	4.63	117.5	4.63	117.5	5.51	140	5.51	140
High curved canopy	n/a	n/a	4.63	117.5	4.63	117.5	4.63	117.5	n/a	n/a	n/a	n/a

ROOM OUTPUT WHEN FITTED WITH BOILERS AS LISTED BELOW

<u>BOILER OUTPUTS IN BTU'S</u>		4.5Kw		6.0Kw		9.0Kw		12.0Kw		16.0Kw		20.0Kw	
8,000	Slab boiler	3.5Kw		4.5Kw		7.0Kw		10.0Kw		13.5Kw		17.5Kw	
20,000	Slab boiler	-		3.7Kw		5.9Kw		7.2Kw		11.5Kw		13.9Kw	
27,000	Slab Boiler	-		-		-		6.5Kw		8.5Kw		11.0Kw	
25,000	Split saddle	-		3.1Kw		-		-		-		-	
30,000	Split saddle	-		-		4.5Kw		-		-		-	
35,000	Split saddle	-		-		-		5.8Kw		-		-	
42,000	Split saddle	-		-		-		-		6.8Kw		-	
53,000	Split saddle	-		-		-		-		-		7.0Kw	

ROOF BOILERS DESIGNED TO BE USED IN CONJUNCTION WITH RELEVANT SPLIT SADDLE BOILERS DETAILED ABOVE PROVIDING ROOM OUTPUTS AS LISTED BELOW

8-12,000	Roof boiler total	38,000Btu's	to water	2.20Kw	-	-	-
10-15,000	Roof boiler total	45,000Btu's	to water	-	2.60Kw	-	-
12-18,000	Roof boiler total	54,000Btu's	to water	-	-	3.30Kw	-
17-22,000	Roof boiler total	70,000Btu's	to water	-	-	-	3.70Kw

FIREVIEW FREESTANDING STOVES - BOILER SPECIFICATIONS

Flue and boiler spigot centres taken from the rear

Fireview Model		4.5Kw		6.0Kw		9.0Kw		12.0Kw		16.0Kw		20.0Kw	
		inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
Returns	A	6.73	171	6.65	169	7.05	179	7.00	179	7.99	203	8.35	212
Flows slab	B	15.87	403	12.95	329	13.35	339	13.35	339	14.33	364	14.65	372
Flows saddle	C	n/a	n/a	n/a	n/a	18.39	467	18.35	467	20.67	525	23.82	605
Widths slab	D	n/a	n/a	7.24	184	7.24	184	7.24	184	7.24	184	7.24	184
Widths saddle	E	n/a	n/a	n/a	n/a	18.98	482	20.47	520	22.99	584	11.65	296
Widths 20.0Kw only	G	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	24.80	630
Widths 4.5Kw only	H	4.50	114.5	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Flue centres	F	13.19	335	18.23	463	18.62	473	18.62	473	20.35	517	20.35	517
Widths roof boiler	X	n/a	n/a	n/a	n/a	18.98	482	20.47	520	22.99	584	18.50	470
Returns roof boiler	Y	n/a	n/a	n/a	n/a	27.28	693	27.28	693	29.17	741	29.17	741
Flows roof boiler	Z	n/a	n/a	n/a	n/a	27.68	703	27.68	703	28.78	731	28.78	731
Flue size		5.00	127	6.00	152	6.00	152	6.00	152	7.00	178	7.00	178

