











STOVE	Min-Max Output kW	Flue Outlet Internal Ø mm Rear	Flue Outlet Internal Ø mm Top	Weight kg	Standard Leg Length mm	Leg Options mm	Ashpan	Ash Shelf	Childproof Fire Door	Fuel: Wood & Briquettes	Fuel: Smokeless Fuel	Max Log Length cm	W (Width) mm	H (Height) mm	D (Depth) mm	D (Without Ashplate)	RF (Rear Flue) mm	TF (Top Flue) mm	RW INSET (Rear Width)	RH INSET (Rear Height)	Tappings to Boilered Models mm (i) horizontal centreline	(ii) from topto centreline	(iii) vertical centreline	(iv) tapping diameter	Boiler Outputs BThUs
Squirrel Cleanheat 1430	3-6	125	125	72	100	150/250	•	•		•	•	28	388	546	415	345	439	102	-	-	230	53	263	39	8000
Squirrel Convector 1440	2-5	125	125	85	N/A	N/A	•	•		•	•	28	435	715	415	395	605	102	-	-	-	-	-	-	-
Squirrel Standard Airwash 1410	2-4	125	125	70	100	150/250	•	•		•	•	28	388	546	415	345	439	102	-	-	230	53	263	39	8000
Badger Cleanheat Convector 3140	3-6	155	155	110	N/A	N/A	•	•	•	•	•	32	514	739	495	433	613	161	-	-	-	-	-	-	-
Badger Cleanheat 3110	3-6	155	155	95	150	210	•	•	•	•	•	32	440	615	495	433	489	161	-	-	-	-	-	-	-
Owl Cleanheat 3410	4-7	155	155	110	210	100	•	•	•	•	•	38	487	688	495	415	562	147	-	-	-	-	-	-	-
Owl Cleanheat 3450 Soapstone	4-7	155	155	180	N/A	N/A	•	•	•	•	•	37	554	739	495	415	613	147	-	-	-	-	-	-	-
Owl Cleanheat Convector 3440	4-7	155	155	120	N/A	N/A	•	•	•	•	•	38	554	739	495	415	613	147	-	-	-	-	-	-	-
Panther Cleanheat 2130	4-8	155	155	110	150	250	•	•	•	•	•	48	605	605	530	430	430	130	-	-	385	115	185	39	7000 24000
Panther Cleanheat Convector 2140	4-8	155	155	120	N/A	N/A	•	•	•	•		48	575	715	530	440	540	130	-	-	-	-	-	-	-
Swan Cleanheat 5010	4-7	155	155	110	150	100/250	•	•	•	•		40	480	625	470	390	445	120	-	-	-	-	-	-	-
Morso 5060 Inset Cleanheat Convector	4-8	155	-	115	N/A	N/A	•		•	•		35	645	592	420	-	-	160	590	530	-	-	-	-	-
Morso 4560 Inset Cleanheat Convector	3-6	155	-	93	N/A	N/A	•		•	•		25	516	629	395	-	-	158	490	595	-	-	-	-	-
Morso 3610	3-16	155	155	220	250	N/A	•	•	•	•		60	749	797	638	535	660	183	-	-	-	-	-	-	-
Dove Cleanheat 1630	7-12	155	155	135	150	100/250	•	•		•	•	50	664	695	522	436	530	195	-	-	500	52	250	39	3400
Morso 4640 Cleanheat Convector	3-6	155	155	115	N/A	N/A	•		•	•		33	490	800	410	-	705	140	-	-	-	-	-	-	-
Morso 4600 Cleanheat Convector	3-6	155	155	115	N/A	N/A	•		•	•		33	490	895	410	-	800	140	-	-	-	-	-	-	-
Panther Gas	4.9 NG	155	155	90	150	250	N/A	N/A	•	N/A	N/A	N/A	605	605	530	-	460	130	-	-	-	-	-	-	-
	4.9 LPG																				-	-	-	-	-
Squirrel Gas	3.8 NG	125	125	60	100	150/250	N/A	N/A		N/A	N/A	N/A	388	546	415	-	439	102	-	-	-	-	-	-	-
	3.4 LPG																				-	-	-	-	-
Squirrel Gas Balanced Flue	3.6 NG	155	-	60	100	150/250	N/A	N/A		N/A	N/A	N/A	388	546	415	-	439	-	-	-	-	-	-	-	-